Kris De Brabanter
Iowa State University
Department of Statistics & Computer Science
2419 Snedecor Hall, Ames, IA, 50011-1210

kbrabant@iastate.edu

Johan A.K. Suykens & Bart De Moor
Katholieke Universiteit Leuven
Department of Electrical Engineering, ESAT-STADIUS
Kasteelpark Arenberg 10, B-3001 Leuven-Heverlee, Belgium

{johan.suykens,bart.demoor}@esat.kuleuven.be

StatLSSVM User's Guide



October 8, 2013

Chapter 1

Overview of functions in StatLSSVM

Function Call	Short explanation	Page
bimodNW	Internal function. Estimate a regression curve based on bimodal kernels	
bitreverse32	Internal function. Reverse the bits of the argument	
changelssvm	Change a field of the object oriented representation of the LS-SVM	9
cilssvm	Constructs pointwise or simultaneous confidence intervals	10
crossval	Estimate performance of an LS-SVM with fast v-fold CV	11
crossval2lp1	Estimate performance of an LS-SVM with leave-$2l+1$-out CV	12
csa	Coupled simulated annealing with variance control	13
cvl	Calculate l for leave-$2l+1$-out CV	14
densitylssvm	One dimensional density estimation via regression	15
densitylssvm2d	Two dimensional density estimation via regression	17
epdfhist	Emperical density estimate	19
gcrossval	Estimate performance of an LS-SVM with generalized CV	20
hall	Estimate error variance model free using Hall's estimator	21
huber	Huber's loss function	22
initlssvm	Initiate LS-SVM object interface	23
kernel_matrix	Construct the positive (semi-) definite and symmetric kernel matrix	24
kernel_matrix2	Internal function. Fast evaluation of the kernel matrix	
latticeseq_b2	Internal function. Generate points from a lattice sequence in base 2 in radical inverse ordering.	
leaveoneout	Estimate performance of an LS-SVM with fast leave-one-out CV	25
linf	L_∞ norm	22
lscvhist	Tune number of bins for 1d or 2d histograms based on least squares CV	26
lssvmMATLAB	Internal function. Matlab implementation of the LS-SVM solver	
mae	Mean absolute error	22
mse	Mean squared error	22
plotlssvm	Plot LS-SVM results	27
plotlssvmadd	Plot additive LS-SVM results	28
progress	Internal function. Text progress bar	
rcrossval	Estimate performance of an LS-SVM with robust v-fold CV	29
regdata2d	Transform a 2d density estimation problem in a regression problem	30
robustlssvm	Robust training of LS-SVM via iterative reweighting	31
rsimplex	Derivative-free simplex method for robust tuning	32
simlssvm	Evaluate LS-SVM at arbitrary points	33
simplex	Derivative-free simplex method for standard LS-SVM tuning	32
smootherlssvm	Calculate smoother matrix for LS-SVM	34
statgetargs	Internal function. Process parameter name/value pairs for density estimation	
tbform	Volume-of-tube formula	35
trainlssvm	training of LS-SVM	36

`tunelssvm`	Find suitable tuning parameters of LS-SVM	37
`weightingscheme`	Internal function. Weighting functions used by `robustlssvm`	

Chapter 2

Overview of data sets in StatLSSVM

All the data sets below can be found on http://www.uow.edu.au/~mwand/webspr/data.html except for the `faithful`, `birth` and `beluga` data sets. The latter can be found on http://research.microsoft.com/en-us/um/people/cmbishop/prml/webdatasets/faithful.txt and http://pages.stern.nyu.edu/~jsimonof/SmoothMeth/Data/Tab/ respectively.

Data set	Description and characteristics
`diabetes`	Factors affecting patterns of insulin-dependent diabetes mellitus in children. The response measurement is the logarithm of C-peptide concentration (pmol/ml) at diagnosis, and the predictor measurements are age and base deficit (a measure of acidity). The data set consist out of 43 measurements and has three columns: • `age` : age of the children • `base deficit` : measure of acidity • `Cpeptide` : response measurement
`LIDAR`	The `LIDAR` data set has 221 observations from a light detection and ranging (LIDAR) experiment. The data set contains the following columns: • `range` : distance travelled before the light is reflected back to its source • `logratio` : logarithm of the ratio of received light from two laser sources
`UStemp`	The UStemp data set has 56 observations on the temperature and location of 56 U.S. cities. This data frame contains the following columns: • `latitude` : degrees latitude (north of Equator) • `longitude` : (negative) degrees longitude (west of Greenwich) • `min.temp` : average minimum January temperature
`fossil`	The fossil data set has 106 observations on fossil shells. This data frame contains the following columns: • `age` : age in millions of years • `strontium.ratio` : ratios of strontium isotopes

`nba` The NBA data set has 96 observations on mean points scored per minute conditional on the number of minutes played per game and height in centimeters for 96 NBA players who played the guard position during the 1992-1993 season.

- `mpg` : minutes played per game
- `height` : height in centimeters
- `mps` : mean points scored per minute

`nba2` The NBA2 data set has 96 observations assists per minute and points per minute for 96 NBA players who played the guard position during the 1992-1993 season.

- `apm` : assists per minute
- `ppm` : points per minutes

`faithful` Old Faithful Geyser data set. Duration of the eruption for the Old Faithful geyser in Yellowstone National Park, Wyoming, USA. The data set has 272 observations.

- `eruptions` : Eruption time in minutes

`birth` U.S. monthly birth rate for the period from January 1940 through December 1947. This data set contains 96 observations.

- `year` : year of birth
- `birthrate` : birth rate

`beluga` Nursing time (in seconds) of a newborn beluga whale calf Hudson to the time after birth, where time is measured is six-hour time periods. This data set contains 228 observations.

- `period` : six-hour time periods
- `nursingtime` : Nursing time (in seconds)

Chapter 3

General notation

In the full syntax description of the function calls, a star (*) indicates that the argument is optional. In the description of the arguments, a (*) denotes the default value. In this extended help of the function calls of `StatLSSVM`, a number of symbols and notations return in the explanation and the examples. These are defined as follows:

Variables	**Explanation**
`d`	Dimension of the input vectors
`m`	Dimension of the output vectors
`n`	Number of training data
`nt`	Number of test data
`X`	`N`×`d` matrix with the inputs of the training data
`Xt`	`Nt`×`d` matrix with the inputs of the test data
`Y`	`N`×`m` matrix with the outputs of the training data
`Yt`	`Nt`×`m` matrix with the outputs of the test data

This toolbox supports an object oriented interface. This has a few dedicated structures which will appear many times:

Structure	**Explanation**
`model`	Object oriented representation of the LS-SVM model

Chapter 4

Alphabetical list of function calls

4.1 changelssvm

Purpose

Change a field of the object oriented representation of the LS-SVM

Description and full syntax

The fields of the model structure can be altered by this function.

```
>> model = changelssvm(model,'field','value')
```

An alternative to change the field(s) is to use

```
>> model.<field> = <value>
```

The different options are given in the following table:

- General options representing the kind of model:

```
          status: Status of this model ('trained'  or 'changed' )
           alpha: Support values of the trained LS-SVM model
               b: Bias term of the trained LS-SVM model
        duration: Number of seconds the training lasts
             gam: Regularisation parameter
     kernel_type: Kernel function
       bandwidth: bandwidth of the kernel function
         weights: Weighting function for robust regression
```

- Fields used to specify the data:

```
           x_dim: Dimension of input space
           y_dim: Dimension of responses
         nb_data: Number of training data
          xtrain: Inputs of training data
          ytrain: Outputs of training data
```

See also:

initlssvm

4.2 cilssvm

Purpose

Construction of bias corrected $100(1-\alpha)\%$ *pointwise or simultaneous confidence intervals*

Description

This function calculates bias corrected $100(1-\alpha)\%$ pointwise or simultaneous confidence intervals. The bias is estimated by the principle of double smoothing with a fourth order kernel based on the Gaussian. The procedure supports homoscedastic data as well as heteroscedastic data. The construction of pointwise confidence intervals are based on the central limit theorem for linear smoothers combined with bias correction and variance estimation. The volume-of-tube formula is used for the construction of simultaneous confidence intervals. In this case, the bands are expanded to account for bias rather than recentered to obtain proper coverage.

Full syntax

```
>> ci = cilssvm(model)
>> ci = cilssvm(model, alpha)
>> ci = cilssvm(model, alpha, conftype)
>> ci = cilssvm(model, alpha, conftype,vartype)
```

Outputs

`ci`	$n \times 2$ matrix containing the lower and upper confidence intervals

Inputs

`model`	Object oriented representation of the LS-SVM model
`alpha`(*)	Significance level (by default 5%)
`conftype`(*)	Type of confidence interval 'pointwise' or 'simultaneous' (by default 'simultaneous')
`vartype`(*)	'homoscedastic' or 'heteroscedastic' (by default 'homoscedastic')

See also:

`trainlssvm, simlssvm, tbform`

References

[1] Hall P. & Marron S. (1990), On variance estimation in nonparametric regression, *Biometrika*, 77, 415-419.

[2] Sun J. & Loader C.R. (1994), Simultaneous confidence bands for linear regression and smoothing, *Annals of Statistics*, 22(3), 1328-1345.

[3] Krivobokova, T., Kneib, T. & Claeskens, G. (2010). Simultaneous confidence bands for penalized spline estimators. *Journal of the American Statistical Association*, 105(490), 852–863.

[4] De Brabanter K., De Brabanter J., Suykens J.A.K. & De Moor B. (2011), Approximate confidence and prediction intervals for least squares support vector regression. *IEEE Transactions on Neural Networks*, 22(1), 110–120.

4.3 crossval

Purpose

Estimate performance of an LS-SVM with fast v-fold cross-validation

Full syntax

This function is a fast implementation of v-fold CV which uses previously computed results. `crossval` can only be used in combination with `tunelssvm` (see p. 37). The command can be invoked as follows:

```
>> model = tunelssvm(model,'crossval')
```

See also:

`leaveoneout, gcrossval, rcrossval, crossval2lp1, tunelssvm`

References

[1] An S., Liu W., & Venkatesh S. (2007), Fast cross-validation algorithms for least squares support vector machine and kernel ridge regression. *Pattern Recognition*, 40(8), 2154–2162

[2] De Brabanter K., De Brabanter J., Suykens J.A.K. & De Moor, B. (2010), Optimized fixed-size kernel models for large data sets. *Computational Statistics & Data Analysis*, 54(6), 1484–1504

4.4 crossval2lp1

Purpose

Estimate performance of an LS-SVM with leave-$2l+1$-out cross-validation in the presence of correlated errors

Full syntax

This function is a fast implementation of leave-$2l+1$-out cross-validation which uses previously computed results. `crossval2lp1` can only be used in combination with `tunelssvm` (see p. 37). The command can be invoked as follows:

```
>> model = tunelssvm(model,'crossval2lp1')
```

See also:

`leaveoneout, crossval, gcrossval, rcrossval, tunelssvm`

References

[1] Chu, C.K. and Marron, J.S. (1991). Comparison of two bandwidth selectors with dependent errors. *Annals of Statistics*, 19(4), 1906-1918.

[2] De Brabanter K., De Brabanter J., Suykens J.A.K., De Moor B. (2011), Kernel regression in the presence of correlated errors. *Journal of Machine Learning Research*, 12, pp. 1955–1976.

4.5 csa

Purpose

Coupled simulated annealing finds the minimum of the functions `crossval, rcrossval, gcrosval, leaveoneout` *and* `crossval2lp1` *when used with* `tunelssvm`*.*

Description

The optimization process consists out of two steps: first, determine good initial starting values by means of coupled simulated annealing (CSA) and second, perform a fine-tuning derivative-free simplex search using the previous end result as starting values. In contrast to other global optimization techniques CSA is not slow and can easily escape from local minima. Since its working principle is based on coupled multiple starters it is more effective than multi-start gradient descent optimization algorithms. Another advantage of CSA is that it uses the acceptance temperature to control the variance of the acceptance probabilities with a control scheme that can be applied to an ensemble of optimizers. This leads to an improved optimization efficiency because it reduces the sensitivity of the algorithm to the initialization parameters while guiding the optimization process to quasi-optimal runs. Because of the effectiveness of the combined methods only a small number of iterations iterations are needed to acquire a suitable set of smoothing parameters (bandwidth h of the kernel and the regularization parameter γ).

References

[1] Xavier-de-Souza S., Suykens J.A.K., Vandewalle J. & Bolle D. (2010), Coupled simulated annealing. *IEEE Transactions on Systems, Man, and Cybernetics - Part B*, 40(2), 320–335.

[2] Xavier-de-Souza S., *Optimisation and Robustness of Cellular Neural Networks*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Jun. 2007, 229 p.

4.6 cvl

Purpose

Find an estimate of l in leave-$2l+1$-out cross-validation based on bimodal kernels.

Description

Finds an estimate of l in leave-$2l+1$-out cross-validation for regression with correlated errors. The method is based on the use of bimodal kernels [2] and the fact that the quantity

$$\left| \frac{\sum_{i=1}^{n-q} \hat{e}_i \hat{e}_{i+q}}{\sum_{i=1}^{n} \hat{e}_i^2} \right| \leq \frac{\Phi^{-1}(1-\frac{\alpha}{2})}{\sqrt{n}},$$

where $\hat{e}_i$ denotes the ith residual, $q \geq 1$, Φ^{-1} denotes the quantile function of the standard normal distribution and α is the significance level [1].

Full syntax

```
>> [l,index] = cvl(X,Y)
```

Outputs

`l`	Optimal l in leave-$2l+1$-out CV
`index`(*)	Indices for leave-$2l+1$-out CV used in `crossval2lp1` (depends on l)

Inputs

`X`	Input data
`Y`	Output data

See also:

`crossval2lp1`

References

[1] Kendall M.G., Stuart A. & Ord J.K. (1983), *The Advanced Theory of Statistics, vol. 3, Design and Analysis, and Time-Series* (4th ed.), Griffin, London.

[2] De Brabanter K., De Brabanter J., Suykens J.A.K., De Moor B. (2011), Kernel regression in the presence of correlated errors. *Journal of Machine Learning Research*, 12, pp. 1955–1976.

4.7 densitylssvm

Purpose

One dimensional density estimation based on a regression approach

Description

The connection between density estimation on an interval and regression is established via a binning technique. The interval $[a, b]$ is partitioned into N subintervals of equal length $\delta = (b - a)/N$, where N is determined via Silvermans's rule of thumb or least squares cross-validation. Via this technique the density estimation problem is converted in to a nonparametric heteroscedastic regression problem. In order the deal with the heteroscedasticity Anscombe's variance stabilizing transformation is used to the bin count. Also, the empirical density estimate (requires `Matlab` statistics toolbox) is plotted with the smoothed density. When estimating the cumulative distribution function (requires `Matlab` statistics toolbox) and the plot command is set to `on`, the function also returns 95% uniform confidence intervals for the empirical cumulative distribution function which are based on the DKW inequality.

Full syntax

- General syntax

```
>> [model,C,f,xi,Nbin] = densitylssvm(X)
```

Outputs

`model`	Object oriented representation of the LS-SVM model
`C`(*)	Normalization constant such that the estimated function is a density
`f`(*)	Vector of density values
`xi`(*)	Values at which the density estimate is evaluated
`Nbin`(*)	Number of bins used in the histogram

Inputs

`X`	Input data (one dimensional)

- Advanced syntax

```
>> [model,C,f,xi,Nbin] = densitylssvm(X,'name','value')
```

By adding extra inputs one can specify one or more optional parameter name/value pairs to control the density estimation. Valid parameter strings and their possible values are as follows:

name	value
`nbin`	Method to determine the number of bins. By default least squares CV (`'lscv'`) is used. Another possibility is Silvermans's rule of thumb (`'reference'`)
`function`	By default probability density function (`'pdf'`) is set. Other possibility is to estimate the cumulative distribution function (`'cdf'`)
`support`	By default `'unbounded'`. This allows the density to extend over the whole real line. When setting this option to `'positive'` will restrict the density to positive values (only valid for pdf)
`points`	The number of equally spaced points in xi. Default is 100
`figure`	Plot result: `'on'` (default), `'off'`

See also:

`trainlssvm, lscvhist, densitylssvm2d, regdata2d`

References

[1] Anscombe F.J. (1948), The transformation of Poisson, Binomial and Negative-Binomial data. *Biometrika*, 35:246-254.

[2] Fan J. & Gijbels I (1996). *Local Polynomial Modelling and Its Applications.* Chapman & Hall.

[3] Silverman B.W. (1992). *Density Estimation for Statistics and Data Analysis.* Chapman & Hall, 1st edition, (reprinted).

[4] Wasserman L. (2006), *All of Nonparametric Statistics*, Springer.

[5] De Brabanter K., Sahhaf S., Karsmakers P., De Brabanter J., Suykens J.A.K. & De Moor B., Nonparametric comparison of densities based on statistical bootstrap, in *Proc. of the Fourth European Conference on the Use of Modern Information and Communication Technologies (ECUMICT)*, Gent, Belgium, Mar. 2010, pp. 179–190.

4.8 densitylssvm2d

Purpose

Two dimensional density estimation based on a regression approach

Description

The connection between density estimation on an interval and regression is established via a binning technique. The interval $[a, b] \times [c, d]$ is partitioned into equal (default) or unequal subintervals. Via this technique the density estimation problem is converted in to a nonparametric heteroscedastic regression problem. In order the deal with the heteroscedasticity Anscombe's variance stabilizing transformation is used to the bin count. By default the number of bins is tuned via least squares cross-validation.

Full syntax

- General syntax

```
>> [model,C,f,xi,Nbin] = densitylssvm(X)
```

Outputs

`model`	Object oriented representation of the LS-SVM model
`C`(*)	Normalization constant such that the estimated function is a density
`f`(*)	Vector of density values
`xi`(*)	Values at which the density estimate is evaluated
`Nbin`(*)	Number of bins used in the histogram

Inputs

`X`	Input data (two dimensional)

- Advanced syntax

```
>> [model,C,f,xi,Nbin] = densitylssvm(X,'name','value')
```

By adding extra inputs one can specify one or more optional parameter name/value pairs to control the density estimation. Valid parameter strings and their possible values are as follows:

name	value
`nbin`	Method to determine the number of bins. – `'lscvequal'` (default): least squares cross-validation with equal ♯bins – `'lscvunequal'` : least squares cross-validation with unequal ♯bins – `'reference'` : Rule of thumb incorporating correlation (see [5, p. 84]) – `[nbin1 nbin2]` : user defined ♯bins
`points`	The number of equally spaced points in xi. Default is 256
`figure`	Plot result: `on` (default), `off`

See also:

`trainlssvm, lscvhist, densitylssvm, regdata2d`

References

[1] Anscombe F.J. (1948), The transformation of Poisson, Binomial and Negative-Binomial data. *Biometrika*, 35:246-254.

[2] Fan J. & Gijbels I (1996). *Local Polynomial Modelling and Its Applications*. Chapman & Hall.

[3] Silverman B.W. (1992). *Density Estimation for Statistics and Data Analysis*. Chapman & Hall, 1st edition, (reprinted).

[4] De Brabanter K., Sahhaf S., Karsmakers P., De Brabanter J., Suykens J.A.K. & De Moor B., Non-parametric comparison of densities based on statistical bootstrap, in *Proc. of the Fourth European Conference on the Use of Modern Information and Communication Technologies (ECUMICT)*, Gent, Belgium, Mar. 2010, pp. 179–190.

[5] Scott D.W. (1992), Multivariate Density Estimation: Theory, Practice, and Visualization, John Wiley & Sons.

4.9 epdfhist

Purpose

Construct empirical density estimate

Description

Construction of the empirical density estimate. By default, the number of bins are determined by Scott's rule (but can also be user defined). This function requires the Statistics toolbox from `Matlab`.

Full syntax

```
>> epdfhist(X)
>> epdfhist(X,Nbin)
```

Outputs

	Histogram plot of the emperical density estimate

Inputs

`X`	Input data (one dimensional)
`Nbin`(*)	User defined ♯bins

See also:

`densitylssvm, densitylssvm2d, lscvhist, regdata2d`

References

[1] Cox, D.R. & Oakes D. (1984). *Analysis of Survival Data*. London, Chapman & Hall.

4.10 gcrossval

Purpose

Estimate performance of an LS-SVM with generalized cross-validation

Full syntax

This function is a fast implementation of generalized CV which uses previously computed results. `gcrossval` can only be used in combination with `tunelssvm` (see p. 37). The command can be invoked as follows:

```
>> model = tunelssvm(model,'gcrossval')
```

See also:

`leaveoneout, crossval, rcrossval, crossval2lp1, tunelssvm`

References

[1] Craven P. & Wahba G. (1979), Smoothing noisy data with spline functions, *Numerische Mathematik*, 31(4), 377-403.

[2] Golub G.M., Heath M. & Wahba G. (1979), Generalized cross-validation as a method for choosing a good ridge parameter, *Technometrics*, 21(2), 215-223.

[3] De Brabanter K., *Least Squares Support Vector Regression with Applications to Large-Scale Data: a Statistical Approach*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Apr. 2011, 246 p.

4.11 hall

Purpose

Calculate the error variance model free using Hall's estimator

Description

Calculate the error variance in 1d model free using Hall's estimator which is $\sqrt{n}$-consistent. Consider the data $\{(X_1, Y_1), \ldots, (X_n, Y_n)\}$. First, the input data is sorted, i.e. $X_1 \leq \ldots \leq X_n$, and the output data is sorted accordingly. Second, the estimated error variance $\hat{\sigma}^2$ is calculated as

$$\hat{\sigma}^2 = \frac{1}{n-2} \sum_{i=1}^{n-2} (0.809Y_i - 0.5Y_{i+1} - 0.309Y_{i+2})^2.$$

Full syntax

```
>> var = hall(X,Y)
```

Outputs

`var` Estimated error variance

Inputs

`X` Input data (one dimensional)

`Y` Output data

References

[1] Hall P. & Marron S. (1990), On variance estimation in nonparametric regression, *Biometrika*, 77, 415–419.

[2] Hall P., Kay J.W. & Titterington D.M. (1990), Asymptotically optimal difference-based estimation of variance in nonparametric regression, *Biometrika*, 77(3), 521–528.

4.12 huber, linf, mae, mse

Purpose

Loss functions

Description

A variety of cost measures can be defined

- `huber` $$C_{\text{huber,c}}(e) = \begin{cases} \frac{1}{2}e^2, & |e| \le c; \\ 2c|e| - c^2, & \text{otherwise.} \end{cases}$$
- `mae`: L_1 $$C_{L_1}(e) = \frac{\sum_{i=1}^{n} |e_i|}{n}$$
- `linf`: L_∞ $$C_{L_\infty}(e) = \sup_i |e_i|$$
- `mse`: L_2 $$C_{L_2}(e) = \frac{\sum_{i=1}^{n} e_i^2}{n}$$

The parameter c in Huber's loss function can be user specified or automatically determined (default). If no user specific value is supplied, the parameter is calculated by 1.345MAD(e).

Full syntax

- `>> C = huber(e)`
  `>> C = huber(e,c)`

  Outputs

  `C` Estimated cost

  Inputs

  `e` Input vector, for example residuals (one dimensional)

  `c`(*) User specified parameter c

- `>> C = mse(e)`

  Outputs

  `C` Estimated cost of the residuals

  Calls

  `mse` `mae`, `linf` or `mse`

  Inputs

  `e` Residual vector

See also:

`crossval, rcrossval, gcrossval, crossval2lp1, leaveoneout`

References

[1] Huber P.J. (1964). Robust estimation of a location parameter. *The Annals of Mathematical Statistics*, 35(1), 73-101.

4.13 initlssvm

Purpose

Initialize an LS-SVM model

Full syntax

```
>> model = initlssvm(X, Y, gam, h, kernel)
>> model = initlssvm(X, Y, gam, h, kernel, bwopt)
```

Outputs

model	Object oriented representation of the LS-SVM model

Inputs

X	n×d matrix with the inputs of the training data
Y	n×1 vector with the outputs of the training data
gam	Regularization parameter. Initialize as []
h	Kernel bandwidth. Initialize as [])
kernel(*)	Kernel type (by default 'gauss_kernel'). The following kernels are supported: 'gauss_kernel', 'RBF_kernel' 'gauss4_kernel', 'gaussadd_kernel' and 'lin_kernel'.
bwopt(*)	Single bandwidth ('single') or bandwidth per dimension ('multiple') for additive models. Only valid with 'gaussadd_kernel'. By default 'single'

See also:

changelssvm

4.14 kernel_matrix

Purpose

Construct the positive (semi-) definite and symmetric kernel matrix

Basic Syntax

```
>> Omega = kernel_matrix(X, kernel, h)
```

Description

This matrix should be positive definite if the kernel function satisfies Mercer's condition. Construct the kernel values for all test data points in the rows of `Xt`, relative to the points of `X`.

```
>> Omega_Xt = kernel_matrix(X, kernel, h, Xt)
```

The following kernels are supported

- Gaussian kernel (`gauss_kernel`):

$$K(X_i, X_j) = (2\pi)^{-d/2} \exp\left(-\frac{\|X_i - X_j\|_2^2}{2h^2}\right).$$

- RBF kernel (`RBF_kernel`): (numerically more stable than `gauss_kernel` when d is large)

$$K(X_i, X_j) = \exp\left(-\frac{\|X_i - X_j\|_2^2}{2h^2}\right).$$

- Fourth order kernel based on the Gaussian (`gauss4_kernel`):

$$K(X_i, X_j) = \frac{1}{2}(2\pi)^{-d/2}\left(3 - \frac{\|X_i - X_j\|_2^2}{h^2}\right)\exp\left(-\frac{\|X_i - X_j\|_2^2}{2h^2}\right).$$

- Gaussian additive kernel (`gaussadd_kernel`):

$$\Omega(X_i, X_j) = \sum_{k=1}^{d} K(X_i^{(k)}, X_j^{(k)}),$$

  where $K(\cdot,\cdot)$ is the one dimensional Gaussian kernel and $X_i^{(k)}$ denotes the kth component of the d-dimensional column vector X_i.

- Linear kernel (`lin_kernel`):

$$K(X_i, X_j) = X_i^T X_j.$$

Full syntax

```
>> Omega = kernel_matrix(X, kernel, h)
>> Omega = kernel_matrix(X, kernel, h, Xt)
```

Outputs

`Omega`	`n`×`n` (`n`×`nt`) kernel matrix

Inputs

`X`	`n`×`d` matrix with the inputs of the training data
`kernel`	Kernel type (by default `'gauss_kernel'`)
`h`	Kernel bandwidth (for linear kernel, use `[]`)
`Xt`(*)	`nt`×`d` matrix with the inputs of the test data

4.15 leaveoneout

Purpose

Estimate performance of an LS-SVM with fast leave-one-out cross-validation

Full syntax

This function is a fast implementation of leave-one-out CV which uses previously computed results. `leaveoneout` can only be used in combination with `tunelssvm` (see p. 37). The command can be invoked as follows:

```
>> model = tunelssvm(model,'leaveoneout')
```

See also:

`crossval, gcrossval, rcrossval, crossval2lp1, tunelssvm`

References

[1] Ying Z. & Keong K.C. (2004), Fast leave-one-out evaluation and improvement on inference for LS-SVMs, in *Proc of the 17th International Conference on Pattern Recognition (ICPR)*, Volume 3, pp. 494 - 497.

4.16 lscvhist

Purpose

Tune the number of bins for 1d and 2d histograms based on least squares cross-validation (LSCV)

Full syntax

```
>> [N,fval] = lscvhist(X)
>> [N,fval] = lscvhist(X,a)
>> [N,fval] = lscvhist(X,[],'unequal')
>> [N,fval] = lscvhist(X,a,'unequal')
```

Outputs

`N`	Number of bins. For 1d this is natural number and for 2d this is a vector for unequal ♯bins and a natural number of equal ♯bins
`fval`	Value of the LSCV cost function

Inputs

`X`	One or two dimensional input data
`a`(*)	Specification of the search length for the ♯bins (natural number) for one and two dimensional data i.e., from $1 \rightarrow a$. By default $a = 5\lceil(2n)^{(1/3)}\rceil$
`unequal`(*)	LSCV finds unequal ♯bins for two dimensional data. By default equal ♯bins are taken

See also:

`densitylssvm, densitylssvm2d, regdata2d, epdfhist`

References

[1] Rudemo M. (1982), Empirical choice of histograms and kernel density estimators, *Scandinavian Journal of Statistics*, 9, 65–78.

[2] Bowman A.W. (1984), An alternative method of cross-validation for the smoothing of density estimates, *Biometrika*, 71(2), 353–360.

4.17 plotlssvm

Purpose

Plot the LS-SVM results in the environment of the training data

Basic syntax

```
>> model = plotlssvm(model)
```

Description

The first argument specifies the LS-SVM. If the model does not have status `'trained'`, the training algorithm is first called. One can specify the precision of the plot by specifying the `grain` of the grid. By default this value is 100. The dimensions (`seldims`) of the input data to display can be selected as an optional argument in case of higher dimensional inputs (> 2). A grid will be taken over this dimension, while the other inputs remain constant.

Full syntax

```
>> model = plotlssvm(model)
>> model = plotlssvm(model, plottype)
>> model = plotlssvm(model, plottype, grain)
>> model = plotlssvm(model, plottype, grain, seldims)
```

Outputs

`model`(*)	Trained object oriented representation of the LS-SVM model

Inputs

`model`	Object oriented representation of the LS-SVM model
`plottype`(*)	Specifies type of plot for 2d problems (`surface` or `contour` plot) (by default `surf`)
`grain`(*)	The grain of the grid evaluated to compose the surface (by default `100`)
`seldims`(*)	The principal inputs one wants to span a grid (by default `[1 2]`)

See also:

`trainlssvm, simlssvm, plotlssvmadd`.

4.18 plotlssvmadd

Purpose

Plot the additive LS-SVM results in the environment of the training data

Basic syntax

```
>> model = plotlssvm(model)
```

Description

The first argument specifies the LS-SVM. If the model does not have status `'trained'`, the training algorithm is first called. The output of the function is a plot of each fitted function per dimension. This function works only if the number of dimensions is larger or equal than two. Bands representing twice the pointwise standard error of the estimated curve are also visualized together with the partial residuals i.e. the fitted values for each function plus the overall residuals from the additive model.

Full syntax

```
>> model = plotlssvmadd(model)
>> model = plotlssvmadd(model, axislabels)
```

Outputs

`model`(*)	Trained object oriented representation of the LS-SVM model

Inputs

`model`	Object oriented representation of the LS-SVM model
`axislabels`(*)	Cell of axis names, e.g. {'age','pressure'}. By default each x-axis is labeled as $X_1, \ldots X_d$ and the y-axis $m_1(X_1), \ldots, m_d(X_d)$

See also:

`trainlssvm, simlssvm, plotlssvm`.

4.19 rcrossval

Purpose

Estimate performance of an LS-SVM with fast robust cross-validation

Full syntax

This function is a fast implementation of robust CV which uses previously computed results. `rcrossval` can only be used in combination with `tunelssvm` (see p. 37). It is advised always to use an L_1 loss (`mae`) for this type of CV. The command can be invoked as follows:

```
>> model = tunelssvm(model,'rcrossval',{10,'mae'})
```

See also:

`leaveoneout, gcrossval, crossval, crossval2lp1, tunelssvm`

References

[1] De Brabanter K., Pelckmans K., De Brabanter J., Debruyne M., Suykens J.A.K., Hubert M. & De Moor B. (2009), Robustness of kernel based regression: a comparison of iterative weighting schemes, in *Proc. of the 19th International Conference on Artificial Neural Networks (ICANN)*, pp. 100-110

[2] De Brabanter K., Karsmakers P., De Brabanter J., Pelckmans K., Suykens J.A.K. & De Moor B. (2010), On robustness in kernel based regression, *NIPS 2010 Workshop Robust Statistical Learning*.

[3] De Brabanter K. (2011), *Least Squares Support Vector Regression with Applications to Large-Scale Data: a Statistical Approach*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Apr. 2011, 246 p.

4.20 regdata2d

Purpose

Transforms the 2d density estimation problem in to a regression problem

Basic syntax

```
>> model = plotlssvm(model)
```

Description

This function transforms the 2d density estimation problem, given data X, in to a regression problem with bin centers x and bin numbers (heights) y. The data set (x, y) can then be used for multivariate regression.

Full syntax

```
>> [x,y,Nbin] = regdata2d(X)
>> [x,y,Nbin] = regdata2d(X,options)
```

Outputs

`x`	x-coordinate of the bin center
`y`	y-coordinate (height) of the bin center
`Nbin`(*)	Number of bins

Inputs

`X`	2 dimensional data
`options`(*)	Extra user defined options to determine the number of bins.

The following options are supported

`[x,y,Nbin] = regdata2d(X)`	Number of bins are tuned via reference rule
`[x,y,Nbin] = regdata2d(X,'lscv')`	Number of bins are tuned via LSCV (equal number of bins)
`[x,y,Nbin] = regdata2d(X,'lscv','unequal')`	Number of bins are tuned via LSCV (unequal number of bins)
`[x,y,Nbin] = regdata2d(X,[nbin1 nbin2])`	Number of bins are user defined

See also:

`densitylssvm2d, lscvhist`

References

[1] Rudemo M. (1982), Empirical choice of histograms and kernel density estimators, *Scandinavian Journal of Statistics*, 9, 65–78.

[2] Bowman A.W. (1984), An alternative method of cross-validation for the smoothing of density estimates, *Biometrika*, 71(2), 353–360.

[3] Scott D.W. (1992), *Multivariate Density Estimation: Theory, Practice, And Visualization*, Wiley.

4.21 robustlssvm

Purpose

Robust training in the case of non-Gaussian noise or outliers

Basic syntax

```
>> model = robustlssvm(model)
```

Robustness towards outliers can be achieved by reducing the influence of support values corresponding to large errors. One should first use the function `tunelssvm` with `rcrossval` based on a robust loss function (`mae` or `huber`) so all the necessary parameters are optimally tuned before calling this routine.

Full syntax

```
>> model = robustlssvm(model)
```

Outputs

`model` Robustly trained object oriented representation of the LS-SVM model

Inputs

`model` Object oriented representation of the LS-SVM model

See also:

`trainlssvm, tunelssvm, rcrossval`

References

[1] De Brabanter K., Pelckmans K., De Brabanter J., Debruyne M., Suykens J.A.K., Hubert M. & De Moor B. (2009), Robustness of kernel based regression: a comparison of iterative weighting schemes, in *Proc. of the 19th International Conference on Artificial Neural Networks (ICANN)*, pp. 100-110.

[2] M. Debruyne, A. Christmann, M. Hubert & J.A.K. Suykens (2010), Robustness of reweighted least squares kernel based regression, *Journal of Multivariate Analysis*, 101(2), 447–463.

[3] De Brabanter K., Karsmakers P., De Brabanter J., Pelckmans K., Suykens J.A.K. & De Moor B. (2010), On robustness in kernel based regression, *NIPS 2010 Workshop Robust Statistical Learning*.

[4] De Brabanter K. (2011), *Least Squares Support Vector Regression with Applications to Large-Scale Data: a Statistical Approach*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Apr. 2011, 246 p.

4.22 `rsimplex, simplex`

Purpose

Direct search method that does not use numerical or analytic gradients.

Description

The optimization process consists out of two steps: first, determine good initial starting values by means of coupled simulated annealing (CSA) and second, perform a fine-tuning derivative-free simplex search using the previous end result as starting values. This is a direct search method that does not use numerical or analytic gradients. If l is the length of a vector x, a simplex in l-dimensional space is characterized by the $l+1$ distinct vectors that are its vertices. In two-space, a simplex is a triangle; in three-space, it is a pyramid. At each step of the search, a new point in or near the current simplex is generated. The function value at the new point is compared with the function's values at the vertices of the simplex and, usually, one of the vertices is replaced by the new point, giving a new simplex. This step is repeated until the diameter of the simplex is less than the specified tolerance. `rsimplex` and `simplex` are the same functions except `rsimplex` is specifically used for robust regression in collaboration with `rcrossval`.

Because of the effectiveness of the combined methods only a small number of iterations are needed to acquire a suitable set of smoothing parameters (bandwidth h of the kernel and the regularization parameter γ).

References

[1] Nelder J.A. & Mead R. (1965), A simplex method for function minimization, *Computer Journal*, 7, 308–313.

[2] Lagaria J.C., Reeds J.A., Wright M.H. & Wright P.E. (1998), Convergence Properties of the Nelder-Mead Simplex Method in Low Dimensions, *SIAM Journal of Optimization*, 9(1), 112–147.

4.23 simlssvm

Purpose

Evaluate the LS-SVM at given points

Basic syntax

```
>> Yt = simlssvm(model, Xt)
```

Description

`model` is the object oriented representation of the LS-SVM model and the matrix `Xt` represents the points one wants to predict.

Full syntax

```
>> Yt = simlssvm(model, Xt)
```

Outputs

`Yt`	Vector with predicted output of test data

Inputs

`model`	Object oriented representation of the LS-SVM model
`Xt`	`nt`×`d` matrix with the inputs of the test data

See also:

`trainlssvm, initlssvm, plotlssvm, plotlssvmadd`

4.24 smootherlssvm

Purpose

Calculate smoother matrix for LS-SVM

Basic syntax

```
>> S = smootherlssvm(model)
```

Description

LS-SVM is a linear smoother because it can be represented as $\hat{Y} = SY$ where S is the smoother matrix. This matrix can be used to calculate the error variance and confidence intervals.

Full syntax

```
>> S = smootherlssvm(model)
>> S = smootherlssvm(model, Xt)
```

Outputs

`S`	Smoother matrix

Inputs

`model`	Object oriented representation of the LS-SVM model
`Xt`(*)	`nt`×`d` matrix with the inputs of the test data. If supplied, `S` is the smoother matrix for test data

See also:

`trainlssvm, cilssvm, tbform`

References

[1] De Brabanter K., De Brabanter J., Suykens J.A.K. & De Moor B. (2011), Approximate confidence and prediction intervals for least squares support vector regression, *IEEE Transactions on Neural Networks*, 22(1), 110–120.

[2] De Brabanter K. (2011), *Least Squares Support Vector Regression with Applications to Large-Scale Data: a Statistical Approach*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Apr. 2011, 246 p.

4.25 tbform

Purpose

Calculate width of the bands for simultaneous confidence intervals using the volume-of-tube formula.

Basic syntax

```
>> m = tbform(model)
```

Description

Determines the width of the bands, given a significance level α, for simultaneous/uniform confidence intervals based on the volume-of-tube formula.

Full syntax

```
>> m = tbform(model)
>> m = tbform(model,alpha)
```

Outputs

`m`	Width of the bands

Inputs

`model`	Object oriented representation of the LS-SVM model
`alpha`(*)	significance level. By default 0.05

See also:

`smootherlssvm, cilssvm`

References

[1] Rice S.O. (1939), The distribution of the maxima of a random curve, *American Journal of Mathematics* 61, 409-416.

[2] Sun J. & Loader C.R. (1994), Simultaneous confidence bands for linear regression and smoothing, *Annals of Statistics*, 22(3), 1328-1345.

[3] De Brabanter K. (2011), *Least Squares Support Vector Regression with Applications to Large-Scale Data: a Statistical Approach*, PhD thesis, Faculty of Engineering, K.U.Leuven (Leuven, Belgium), Apr. 2011, 246 p.

4.26 trainlssvm

Purpose

Train the support values and the bias term of an LS-SVM

Basic syntax

```
>> model      = trainlssvm(model)
```

Description

The training is done by

```
>> model = trainlssvm(model)
```

The status of the model checks whether a retraining is needed. The implementation is based on the backslash operator in MATLAB. This operator solves the system of linear equations needed to obtain the Lagrange multipliers and bias term of the LS-SVM model.

Full syntax

```
>> model = trainlssvm(model)
```

Outputs

model(*)	Trained object oriented representation of the LS-SVM model

Inputs

model	Object oriented representation of the LS-SVM model

See also:

simlssvm, initlssvm, changelssvm, plotlssvm, plotlssvmadd

4.27 tunelssvm

Purpose

Tune the tuning parameters of the model with respect to the given performance measure

Basic syntax

```
>> model = tunelssvm(model, costfun)
```

where `model` is the object oriented interface of the LS-SVM and `costfun` represents the model selection criteria e.g. `crossval`, `gcrossval`, `leaveoneout`, `crossval2lp1` or `rcrossval`. The `model` object is created by the command `initlssvm`.

```
model = initlssvm(X,Y,[],[],kernel_type);
```

Description

The complete tuning process goes as follows: First, for every kernel, first Coupled Simulated Annealing (CSA) determines suitable starting points for every method. The search limits of the CSA method are set to $[\exp(-10), \exp(10)]$. Second, these starting points are then given to a simplex method. CSA has already proven to be more effective than multi-start gradient descent optimization. Another advantage of CSA is that it uses the acceptance temperature to control the variance of the acceptance probabilities with a control scheme. This leads to an improved optimization efficiency because it reduces the sensitivity of the algorithm to the initialization parameters while guiding the optimization process to quasi-optimal runs. By default, CSA uses five multiple starters. When the model is tuned, the value of the cross-validation function is added the to model structure as `model.CVcost`.

Full syntax

```
>> model = tunelssvm(model)
>> model = tunelssvm(model, costfun)
>> model = tunelssvm(model, costfun, costargs)
>> model = tunelssvm(model, costfun, costargs, wfun)
```

Outputs

`model`	Tuned object oriented representation of the LS-SVM model

Inputs

`model`	Object oriented representation of the LS-SVM model
`costfun`(*)	Model selection criterion. By default `'crossval'`
`costargs`(*)	Cell with extra cost function arguments. By default `{10,'mse'}` where the first argument denotes the number of folds to be used in the `'crossval'` routine and the second argument specifies its loss function
`wfun`(*)	Weight function for robust regression (by default `'wmyriad'`). The weight function can only be used with `'rcrossval'`. Supported weight functions: `'whuber'`, `'whampel'`, `'wlogistic'`, `'wmyriad'`

The four different weights functions are visualized in Table 4.1

When no options are specified for the model selection criteria, the software automatically takes an L_2 (L_1) loss with 10-fold cross-validation if `crossval` (or `rcrossval`) is taken respectively. The following list summarizes the possibilities with the `tunelssvm` command.

Table 4.1: Definitions for the Huber ($\beta \in \mathbb{R}^+$), Hampel, Logistic and Myriad ($\delta \in \mathbb{R}_0^+$) weight functions $V(\cdot)$. The corresponding loss $L(\cdot)$ and score function $\psi(\cdot)$ are also given.

	Huber	Hampel	Logistic	Myriad
$V(r)$	$\begin{cases} 1, & \text{if } \lvert r\rvert < \beta; \\ \frac{\beta}{\lvert r\rvert}, & \text{if } \lvert r\rvert \geq \beta. \end{cases}$	$\begin{cases} 1, & \text{if } \lvert r\rvert < b_1; \\ \frac{b_2 - \lvert r\rvert}{b_2 - b_1}, & \text{if } b_1 \leq \lvert r\rvert \leq b_2; \\ 0, & \text{if } \lvert r\rvert > b_2. \end{cases}$	$\frac{\tanh(r)}{r}$	$\frac{\delta^2}{\delta^2 + r^2}$
$\psi(r)$				
$L(r)$	$\begin{cases} r^2, & \text{if } \lvert r\rvert < \beta; \\ \beta\lvert r\rvert - \frac{1}{2}\beta^2, & \text{if } \lvert r\rvert \geq \beta. \end{cases}$	$\begin{cases} r^2, & \text{if } \lvert r\rvert < b_1; \\ \frac{b_2 r^2 - \lvert r^3\rvert}{b_2 - b_1}, & \text{if } b_1 \leq \lvert r\rvert \leq b_2; \\ 0, & \text{if } \lvert r\rvert > b_2. \end{cases}$	$r\tanh(r)$	$\log(\delta^2 + r^2)$

- Standard tuning with 10-fold cross-validation with an L_2 and L_1 loss

```
>> model = tunelssvm(model)
>> model = tunelssvm(model,'crossval')
>> model = tunelssvm(model,'crossval',{10,'mse'})
>> model = tunelssvm(model,'crossval',{10,'mae'})
```

- Standard tuning with leave-one-out cross-validation with an L_2 and L_1 loss

```
>> model = tunelssvm(model,'leaveoneout')
>> model = tunelssvm(model,'leaveoneout',{'mse'})
>> model = tunelssvm(model,'leaveoneout',{'mae'})
```

- Standard tuning with generalized cross-validation with an L_2 and L_1 loss

```
>> model = tunelssvm(model,'gcrossval')
>> model = tunelssvm(model,'gcrossval',{'mse'})
>> model = tunelssvm(model,'gcrossval',{'mae'})
```

- Robust tuning with different weight functions with robust v-fold cross-validation with an L_1 and Huber loss. If no weight function is specifies myriad weights are taken. It is always advisable to use a robust loss function for robust cross-validation (`mae` or `huber`) in order to obtain a fully robust procedure.

```
>> model = tunelssvm(model,'rcrossval',{10,'mae'})
>> model = tunelssvm(model,'rcrossval',{10,'mae'},'wmyriad')
>> model = tunelssvm(model,'rcrossval',{10,'huber'},'whampel')
>> model = tunelssvm(model,'rcrossval',{10,'mae'},'whuber')
>> model = tunelssvm(model,'rcrossval',{10,'huber'},'wlogistic')
```

- Tuning when errors are correlated with an L_2 and L_1 loss

```
>> model = tunelssvm(model,'crossval2lp1')
>> model = tunelssvm(model,'crossval2lp1',{'mse'})
>> model = tunelssvm(model,'crossval2lp1',{'mae'})
```

See also:

`simlssvm, initlssvm, changelssvm, crossval, gcrossval, rcrossval, leaveoneout, crossval2lp1`